


## SPREADER BEAMS

Telescoping Adjustable Spread - Large Capacity Shackle End

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- ALL Spreader Beams shipped with proof load certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Made in U.S.A.
- Custom designs available - call for engineering.

- ALL lifting equipment individually proof loaded per OSHA requirements.
- Minimum horizontal top rigging angle of 45°
- Ideally suited for adding stability to critical lifts.
- Beam only. Shackles supplied by others.

 Prop 65 – See Page 112



SHOWN WITH OPTIONAL TOP RIGGING & SHACKLES

TELESCOPING ADJUSTABLE LARGE CAPACITY SHACKLE END SPREADER BEAMS							
Working Load Limit in Pounds*	Shackle Size	Model Number Headroom (in) Weight (lbs)	Outside Spread (L) in Feet*				
			Min Max 5'6" - 7'	Min Max 7 - 10	Min Max 10 - 14	Min Max 14 - 20	Min Max 21 - 30
40,000	1-1/2" Top 1-1/2" Bottom	<b>Part Number</b> HR = LBS =	<b>20127</b> 7.6 340	<b>20126</b> 7.6 410	<b>20125</b> 7.6 560	<b>20124</b> 7.6 760	<b>24406</b> 7.6 1275
60,000	1-3/4" Top 1-3/4" Bottom	<b>Part Number</b> HR = LBS =	<b>20132</b> 7.1 395	<b>20131</b> 7.1 490	<b>20130</b> 7.1 660	<b>20129</b> 7.1 890	<b>24407</b> 7.1 1775
80,000	2" Top 2" Bottom	<b>Part Number</b> HR = LBS =	<b>20137</b> 9.3 575	<b>20136</b> 9.3 700	<b>20135</b> 9.3 950	<b>20134</b> 9.3 1,250	<b>24413</b> 9.3 2280
100,000	2" Top 2" Bottom	<b>Part Number</b> HR = LBS =	<b>20142</b> 9.3 575	<b>20141</b> 9.3 700	<b>20140</b> 9.3 950	<b>20139</b> 9.3 1,250	<b>24408</b> 9.3 2437
150,000	2-1/2" Top 2-1/2" Bottom	<b>Part Number</b> HR = LBS =	<b>N/A</b>	<b>24412</b> 13.9 1310	<b>24411</b> 13.9 1640	<b>24410</b> 13.9 2120	<b>24409</b> 13.9 2995

OPTIONAL TOP RIGGING							
Working Load Limit in Pounds*	Part Name		Part Number	Part Number	Part Number	Part Number	Part Number
40,000	<b>Adjustable Spreader</b>		<b>20127</b>	<b>20126</b>	<b>20125</b>	<b>20124</b>	<b>24406</b>
	Wire Rope		23421	23422	23423	23424	24414
	Round Sling Bridle		23433	23434	23435	23436	24422
60,000	<b>Adjustable Spreader</b>		<b>20132</b>	<b>20131</b>	<b>20130</b>	<b>20129</b>	<b>24407</b>
	Wire Rope		23425	23426	23427	23428	24415
	Round Sling Bridle		23437	23438	23439	23440	24423
80,000	<b>Adjustable Spreader</b>		<b>20137</b>	<b>20136</b>	<b>20135</b>	<b>20134</b>	<b>24413</b>
	Wire Rope		23430	23430	23431	23432	24416
	Round Sling Bridle		23441	23442	23443	23444	24424
100,000	<b>Adjustable Spreader</b>		<b>20142</b>	<b>20141</b>	<b>20140</b>	<b>20139</b>	<b>24408</b>
	Wire Rope		23430	23430	23431	23432	24416
	Round Sling Bridle		23441	23442	23443	23444	24424
150,000	<b>Adjustable Spreader</b>		<b>N/A</b>	<b>24412</b>	<b>24411</b>	<b>24410</b>	<b>24409</b>
	Round Sling Bridle		<b>N/A</b>	24418	24417	24426	24425

\*Minimum horizontal top rigging angle is 45° on all fixed and adjustable spreaders. M&W recommends a minimum horizontal top rigging angle of 60°. Adjustable on 6" increments.